

General Description:

This strip light is specially designed for both commercial and industrial use. It can be used in warehouses office, garage, retail, and other commercial applications.

Construction:

All-new high efficiency LED fixture for cost effective lighting for commercial and industrial applications. Delivers 5,120 lumens.

Mounting Options:

Fixture designed for surface, T-Bar, and chain mounting applications.

Specifications:

Housing: All aluminum construction minimizes weight and maximizes thermal performance of the LED light engine.

Finish: All parts are painted with a matte white paint to provide soft, even illumination.

LEDs: Best efficacy of mid level power LEDs, 80+ CRI, utilizes aluminum substrate to provide superior thermal

management.


Features:

- Quick and Easy Installation
- Chain Suspended or Surface Mounting Selectable
- -20° F to 130° F Ambient Opertaing Temperature
- Diffuser in Place
- Suitable for Narrow Architectural Application
- 5 Year Warranty
- Motion Sensor Optional
- Emergency Backup Optional

Ordering Information

Model No.	Length	Application	Watts	Lumens	LPW	Voltage	ССТ	CRI
VFMS4F/32-835	48	4Ft. Linear Strip	32	5120	160	120-277	3500K	82
VFMS4F/32-840	48	4Ft. Linear Strip	32	5120	160	120-277	4000K	82
VFMS4F/32-850	48	4Ft. Linear Strip	32	5120	160	120-277	5000K	82

Mounting Options:



- A Keyhole Sots for Surface Mounting
- B Wiring Knockouts
- C T-Bar Clip Mounting Hole
- D V-Hook Openings for Chain Mounting

Dimmer Connection:

١.	BLACK		BLUE (-)	LED Strip 0-10V DIMMER	
			RED (+)		
N-	WHITE	DRIVER	VIOLET DIM (+)		
			GRAY DIM (-)		